MEDICAL VACUUM SYSTEM

Dry Rotary Vane Vacuum Pump

Rev.2

VAC
PUMPS



VANE
DRY

PRODUCT SPECIFICATION

General Description

NOVAIR USA's industry leading medical vacuum system is designed and manufactured to meet all NFPA 99 standard last edition. The system shall include multiple dry rotary vane vacuum pumps coupled to a direct drive electric motor for continuous duty. Each pump is equipped with an integrated intake filter, check valve, flex hoses and shutoff valve for system isolation to allow maintenance tasks. A.S.M.E. stamp air receiver with gauge and manual drain valve. The system shall include a 3-way tank bypass with pipes and ball valves in bronze or stainless steel. UL certified electrical control panel mounted and wired, controlled by PLC and HMI (Electronic screen or Touch screen). The entire system is 100% tested before leaving the factory.
According to the NFPA 99 standard, it is required to keep one module in reserve, therefore, the capacity of the system is equivalent to the sum of the flow of the total number of modules, minus 1.

Dry (Oil-less) rotary vane vacuum pump, electric motor & air receiver

Dry rotary vane vacuum pump, air cooled with no water requirements and directly driven. Self-lubricating carbon/graphite vanes.
Each pump shall include a quiet operation check valve to prevent backflow, integrated inlet filter, inlet and discharge flex connector, independent anti-vibration bases and shutoff isolation valve. High efficiency compact direct driven motor-pumps for small systems (Up to 2 HP) and High efficiency motor, C-flange TEFC, 1.15 service factor (3HP-15HP). Suitable for electrical service of 208-230/380*/400*/460V, 3 ph, 60 Hz & 190/380 V, 3 ph, 50 Hz. (*optional voltage).
Air receiver A.S.M.E. code stamp, rated for 200 PSIG design pressure, equipped with gauge and manual drain. The receiver comes with a 3-valve by-pass with all pipes and fittings in bronze or stainless steel, as required per NFPA.

Control Panel UL

The system includes a UL listed centralized control panel wired and tested in a NEMA 4 enclosure, through the door disconnect switch, full voltage starter with motor circuit protector and contactor for each motor. Dual control transformer (@ 120 Vac and 24 Vac) Programming Logic Controller (PLC) with Electronic HMI 3.6" resolution 240 x 80 pixel or full color 7" Touch screen HMI resolution 800 x 400 pixel (optional) for system control. Operation mode Manual-Off-Auto and rotation test function. Automatic alternation based on first-on/first-off principle, provision for simultaneous operation or reserve back-up pump if its required. Minimum run-time operation function, with adjustable value to avoid frequent start-stop. Hour meters, run indicator, overload failure indicator and high temperature indicator (optional) for each pump. Back-up transformer failure indicator. Audible and visual alarm with dry contact for remote alarm for general fault.

- Control Panel (NE) **see picture 1**

The control panel includes a 3.6" electronic screen (resolution 240 x 80) with keyboard for system control. It shows the hour meters run indicator and failure indicator, pressure values. Back-up pressure switch for eventual pressure sensor failure.

- Control Panel (NT) (Optional) **see picture 2**

The control panel includes a full color 7" touch screen (resolution 800 x 400) for system control. It shows the hour meters run indicator and failure indicator, pressure values with graphics trends and high alarms indicator. Back-up pressure switch for eventual pressure sensor failure. Datalogger directs to USB memory to file parameters.

- Control Panel (NTW) with Web Communication (Optional) **see picture 2**

It has all the components of control panel (NT) and additionally has Web communication to allow remote internet connectivity to monitoring the system on web-site platform with protected and personalized user and password, accessible from any computer or mobile device for full monitoring.

MADE IN USA

Buffalo U.S.A
www.NOVAIR-USA.com
Info@NOVAIR-USA.com

c UL us LISTED

NFPA MEMBER

MEDICAL VACUUM SYSTEM

Dry Rotary Vane Vacuum Pump

Rev.2

Types of control interfaces

Picture.1 Control Panel NE



Picture 2. Control Panel NT



Additional options available:

- Discharge temperature sensors with screen display value and high discharge air temperature shutdown alarm.
- Two-component epoxy internal coating for corrosion resistance.

VAC

PUMPS

VANE

DRY

PRODUCT SPECIFICATION

MADE IN USA

Buffalo U.S.A
www.NOVAIR-USA.com
Info@NOVAIR-USA.com

c UL us LISTED

NFPA MEMBER